

TRUNKS DISPONIBLES



Admin

Applications

Connectivity

Dashboard

Reports

Settings

UCP

Trunks

This page is used to manage various system trunks

+ Add Trunk -

Name	Tech	CallerID	Status
Sarevoz_in	sip	94000007	Enabled
Sarevoz_out	sip	94000007	Enabled

TRUNK ENTRADA: GENERAL

[Admin](#)[Applications](#)[Connectivity](#)[Dashboard](#)[Reports](#)[Settings](#)[UCP](#)

Edit Trunk

WARNING: This trunk is not used by any routes!

This trunk will not be able to be used for outbound calls until a route is setup that uses it.

Click on [Outbound Routes](#) to setup routing.

[General](#)[Dialed Number Manipulation Rules](#)[sip Settings](#)**Trunk Name** ⓘ**Hide CallerID** ⓘ Yes No**Outbound CallerID** ⓘ**CID Options** ⓘ Allow Any CID Block Foreign CIDs Remove CNAM Force Trunk CID**Maximum Channels** ⓘ**Asterisk Trunk Dial Options** ⓘ Override System**Continue if Busy** ⓘ Yes No**Disable Trunk** ⓘ Yes No

TRUNK ENTRADA: SIP SETTINGS



Admin

Applications

Connectivity

Dashboard

Reports

Settings

UCP

Edit Trunk

WARNING: This trunk is not used by any routes!

This trunk will not be able to be used for outbound calls until a route is setup that uses it.

Click on [Outbound Routes](#) to setup routing.

General

Dialed Number Manipulation Rules

sip Settings

Outgoing

Incoming

Trunk Name ?

Sarevoz_in

PEER Details ?

```
host=194.30.6.32
username='suegraenruso'
secret=estorba
fromuser='suegraenruso'
fromdomain=194.30.6.32
sendrpid=no
type=peer
insecure=invite
directmedia=no
```

TRUNK ENTRADA: REGISTER STRING



Admin

Applications

Connectivity

Dashboard

Reports

Settings

UCP

Edit Trunk

WARNING: This trunk is not used by any routes!

This trunk will not be able to be used for outbound calls until a route is setup that uses it.

Click on [Outbound Routes](#) to setup routing.

General

Dialed Number Manipulation Rules

sip Settings

Outgoing

Incoming

USER Context ⓘ

suegraenruso

USER Details ⓘ

Register String ⓘ

suegraenruso:estorba @194.30.6.32

TRUNK SALIDA: GENERAL

Edit Trunk

In use by 1 route

General

Dialed Number Manipulation Rules

sip Settings

Trunk Name [?](#)

Sarevoz_out

Hide CallerID [?](#)

Yes **No**

Outbound CallerID [?](#)

940000007

CID Options [?](#)

Allow Any CID

Block Foreign CIDs

Remove CNAM

Force Trunk CID

Maximum Channels [?](#)

4

Asterisk Trunk Dial Options [?](#)

T

Override

System


Continue if Busy [?](#)

Yes **No**

Disable Trunk [?](#)

Yes **No**

TRUNK SALIDA: SIP SETTINGS



Edit Trunk

In use by 1 route

General

Dialed Number Manipulation Rules

sip Settings

Outgoing

Incoming

Trunk Name ⓘ

Sarevoz_out

PEER Details ⓘ

```
host=194.30.6.32
username=suegraenuso
secret=estorba
fromuser=suegraenuso
fromdomain=194.30.6.32
sendrpid=pai
type=peer
context=from-trunk-sip-Sarevoz_out
directmedia=no
```

TRUNK SALIDA: SIN CONFIGURACIÓN DE REGISTER



Edit Trunk

In use by 1 route

General

Dialed Number Manipulation Rules

sip Settings

Outgoing

Incoming

USER Context ?

USER Details ?





Register String ?

RUTAS DE SALIDA DISPONIBLES

Outbound Routes

This page is used to manage your outbound routing.

[+ Add Outbound Route](#)

Name	Outbound CID	Attributes
+ sarevoz_out_trunk		   

CONFIGURACIÓN DE RUTA DE SALIDA



Admin

Applications

Connectivity

Dashboard

Reports

Settings

UCP

Outbound Routes

Edit Route

Route Settings

Dial Patterns

Import/Export Patterns

Additional Settings

Route Name ?

sarevoz_out_trunk

Route CID ?

Override Extension ?

Yes

No

Route Password ?

Route Type ?

Emergency

Intra-Company

Music On Hold? ?

default

Time Group ?

---Permanent Route---

Route Position ?

---No Change---

Trunk Sequence for Matched Routes ?

+ Sarevoz_out

+

Optional Destination on Congestion ?

Normal Congestion

Note: Extension Routes is not registered

RUTA DE SALIDA: DIAL PATTERN

[Admin](#)[Applications](#)[Connectivity](#)[Dashboard](#)[Reports](#)[Settings](#)[UCP](#)

Outbound Routes

Edit Route

[Route Settings](#)[Dial Patterns](#)[Import/Export Patterns](#)[Additional Settings](#)

Dial Patterns that will use this Route

Pattern Help

[✎ Dial patterns wizards](#)

(prepend)	prefix		[[6].
(prepend)	prefix		[match pattern

SIP%.CONF: SIEMPRE EL TRUNK DE ENTRADA PRIMERO

```
root@localhost:/etc/asterisk
sendrpid=pai
type=peer
context=from-trunk-sip-sarenetCMB_out

[Sarevoz_in]
host=194.30.6.32
username=
secret=
fromuser=
fromdomain=194.30.6.32
sendrpid=no
type=peer
insecure=invite
context=from-trunk-sip-Sarevoz_in

[Sarevoz_out]
host=194.30.6.32
username=
secret=
fromuser=
fromdomain=194.30.6.32
sendrpid=pai
type=peer
context=from-trunk-sip-Sarevoz_out
```